



EVENT TECHNOLOGY


T-Connect

Equipment:

- 1 CEE-plug 16A 3p 6h
- 1 CEE-socket 16A 3p 6h
- 1 cable entry
(terminal block max. 3x2,5mm²)



Example



IP44 splashproof

94325000


pack.unit: 10



T-Connect

Equipment:

- 1 CEE-plug 16A 3p 6h
- 1 CEE-socket 16A 3p 6h
- 1 cable entry
(terminal block max. 3x2,5mm²)



IP67 watertight

94326000


pack.unit: 10



T-Connect with cable

Equipment:

- 1,5m cable H07RN-F 3G1,5 with CEE-plug 16A 3p 6h
- 1 cable entry
(terminal block max. 3x2,5mm²)
- 1 CEE-socket 16A 3p 6h



IP44 splashproof

IP44 94325001

IP67 watertight

IP67 94326001


pack.unit: 10

T-Connect

2-way connector with cable entry

Equipment:

- 1 cable entry
(terminal block max. 3x2,5mm²)
- 2 CEE-sockets 16A 3p 6h outlet



IP44 splashproof

IP44 94325002

IP67 watertight

IP67 94326002

pack.unit: 10




T-Connect

2-way connector with CEE-plug

Equipment:

- 1 CEE-plug 16A 3p 6h
- 2 CEE-sockets 16A 3p 6h outlet



IP44 splashproof

IP44 94325003

IP67 watertight

IP67 94326003

pack.unit: 10



Event technology MIDNIGHT-SERIES



Compact distribution boxes Series St. Anton

- Plugs and sockets are black

Entry:

1 CEE-plug 16A 5p 400V

Outlet:

3 CEE-sockets 16A 5p 400V

9430052

1 CEE-socket 16A 5p 400V
2 safety sockets 16A 250V

9430053

3 CEE-sockets 16A 3p 230V

9430054

Wall distribution boxes series Salzburg

Dimensions: HxW = 370x298mm

- for wall-fastening
- solid rubber enclosure, with protective roof
- window up to max. 14 modules
- bottom of box and cover connected with joint
- ready wired for connection

IP54 dust- and splashproof

Equipment:

1 CEE-socket 32A 5p 400V sw
1 CEE-socket 16A 5p 400V sw
2 safety sockets 16A 250V sw

1xM32 on top, 1xM32 from bottom

Protection:

1 MCB 32A 3p-C
1 MCB 16A 3p-C
2 MCBs 16A 1p-B
1 RCD 63/4/0,03A over all outlets

92271649



Wall distribution boxes series Bruck

Dimensions: HxW = 370x370mm

- for wall-fastening
- solid rubber enclosure, with protective roof
- window up to max. 18 modules
- bottom of box and cover connected with joint
- ready wired for connection

IP54 dust- and splashproof

Equipment:

1 CEE-socket 32A 5p 400V sw
2 CEE-sockets 16A 5p 400V sw
4 safety sockets 16A 250V sw

1xM32 on top, 1xM32 from bottom

Protection:

1 MCB 32A 3p-C
2 MCBs 16A 3p-C
4 MCBs 16A 1p-B
1 RCD 63/4/0,03A over all outlets

92401543



Mobile distribution boxes series Spitz

Dimensions: HxWxD = 320x320x320mm

- portable, handy solid-rubber mobile box - stackable
- lifting hinged cover with 2 quick acting closures
- maximum safety – closed casing bottom with high ground clearance
- ready wired for connection

IP54 dust- and splashproof

Equipment:

2 CEE-sockets 32A 5p 400V sw
2 CEE-sockets 16A 5p 400V sw
4 safety sockets 16A 250V sw

2m cable 5G6 with
CEE-plug 32A 5p 400V sw

Protection:

2 MCBs 16A 3p-C
4 MCBs 16A 1p-B
1 RCD 63/4/0,03A over all outlets

94741367



Mobile distribution boxes series Steyregg

Dimensions: HxWxD = 79x430x129mm

- portable, handy solid-rubber mobile box
- housing with carrying handle
- ready wired for connection

IP54 dust- and splashproof

Equipment:

2 CEE-sockets 16A 5p 400V sw
2 safety sockets 16A 250V sw

2m cable 5G4 with
CEE-plug 32A 5p 400V sw

Protection:

1 MCB 16A 3p-C
2 MCB 16A 1p-C

9441480

