


Flanged plugs




Power Twist Flanged plug sloping IP66/67

	63 Amp		
	3	4	5
Poles	3	4	5
a	100	100	100
b	112	112	112
c	80	80	80
d	88	88	88
e	8	8	8
f	127	127	127
g	127	127	127
h	80	80	80
i	7	7	7
Connection type: Contact frame with screws			
Wire flexible [mm ²]	6-16		
solid [mm ²]	6-25		
Contact screws [Ncm]	200 Ncm		
Weight [g]	515	566	608

- contact frame with screws
- housing material: PA6
- contacts: nickel-plated contacts, with pilot contact (see page 10)
- for waterproof cover see accessories on page 51

IP66/67 watertight




Power Twist Flanged plug sloping IP66/67

	125 Amp		
	3	4	5
Poles	3	4	5
a	120	120	120
b	130	130	130
c	100	100	100
d	108	108	108
e	8	8	8
f	139	139	139
g	145	145	145
h	100	100	100
i	7	7	7
Connection type: Contact frame with screws			
Wire flexible [mm ²]	16-50		
solid [mm ²]	16-70		
Contact screws [Ncm]	450 Ncm		
Weight [g]	833	942	1044

- contact frame with hexagon socket screws
- housing material: PA6
- contacts: nickel-plated contacts, with pilot contact (see page 10)
- for waterproof cover see accessories on page 51

IP66/67 watertight




b=height
angle=15°

Power Twist Flanged plug IP66/67

	63 Amp		
	3	4	5
Poles	3	4	5
a	271	271	271
b	124	124	124
Connection type: Contact frame with screws			
Wire flexible [mm ²]	6-16		
solid [mm ²]	6-25		
Contact screws [Ncm]	200 Ncm		
Weight [g]	653	704	746

- contact frame with screws
- housing material: PC/ABS
- contacts: nickel-plated contacts, with pilot contact (see page 10)
- for waterproof cover and cable-glands see accessories page 51
- rear entry
- incl. flange gasket

IP66/67 watertight



Power Twist Flanged plug compact IP66/67

	63 Amp		
	3	4	5
Poles	3	4	5
a	116	116	116
b	91	91	91
c	95	95	95
d	70	70	70
e	132	132	132
f	181	181	181
g	70	70	70
h	70	70	70
Øi	6,5	6,5	6,5
Connection type: Contact frame with screws			
Wire flexible [mm ²]	6-16		
solid [mm ²]	6-25		
Contact screws [Ncm]	200 Ncm		
Weight [g]	547	598	640

- contact frame with screws
- housing material: PA6
- contacts: nickel-plated contacts, with pilot contact (see page 10)
- for waterproof cover and cable-glands see accessories page 51
- rear entry
- incl. flange gasket

IP66/67 watertight

110V~
50/60Hz
4h

230V~
50/60Hz
3p=6h
4p+5p=9h

400V~
50/60Hz
3p=9h
4p+5p=6h

500V~
50/60Hz
7h

>50-500V~
100-300Hz
10h

>50-500V~
301-500Hz
2h

Amp.	Poles	pack. unit	Cat.No.	Cat.No.	Cat.No.	Cat.No.	Cat.No.	Cat.No.
------	-------	------------	---------	---------	---------	---------	---------	---------

			110V~	230V~	400V~	500V~	>50-500V~	>50-500V~
flange 100 x 112 - fixing center 80 x 88								
63	3	2	733-4	733-6	733-9	733-7	733-10	733-2
63	4	2	734-4	734-9	734-6	734-7	734-10	734-2
63	5	2	735-4	735-9	735-6	735-7	735-10	735-2



735-6




			110V~	230V~	400V~	500V~	>50-500V~	>50-500V~
flange 120 x 130 - fixing center 100 x 108								
125	3	2	743-4	743-6	743-9	743-7	743-10	743-2
125	4	2	744-4	744-9	744-6	744-7	744-10	744-2
125	5	2	745-4	745-9	745-6	745-7	745-10	745-2



745-6

			110V~	230V~	400V~	500V~	>50-500V~	>50-500V~
H x W x D = 170 x 118 x 124								
63	3	2	77733-4	77733-6	77733-9	77733-7	77733-10	77733-2
63	4	2	77734-4	77734-9	77734-6	77734-7	77734-10	77734-2
63	5	2	77735-4	77735-9	77735-6	77735-7	77735-10	77735-2



77735-6

			110V~	230V~	400V~	500V~	>50-500V~	>50-500V~
flange 116 x 91 - fixing center 95 x 70								
63	3	2	77733-4k	77733-6k	77733-9k	77733-7k	77733-10k	77733-2k
63	4	2	77734-4k	77734-9k	77734-6k	77734-7k	77734-10k	77734-2k
63	5	2	77735-4k	77735-9k	77735-6k	77735-7k	77735-10k	77735-2k



77735-6k