


PowerSyntax®


SINGLE POLE CONNECTOR SERIES



Your idea
is our next
accomplishment



**Power
Syntax®**



Inventors, manufacturers, innovators.


Valentini is a dynamic, ever-evolving company operating in over 60 countries worldwide. For more than 30 years we have actively researched, designed and manufactured connectors for power, signal and hybrid applications.

Our Syntax connectors have been used all over the world to manage power and electric signals in fields such as industry, automotive, broadcasting, shipbuilding & ship to shore power, international sporting events, live shows, military & national emergency management by agencies such as the Italian Civil Protection Department, and so many more.

Valentini is an environmentally-aware company where respect for the environment is an integral part of the manufacturing process. Our team is motivated and mindful of details, as we know details are important in our pursuit of uncompromised quality and utmost reliability.

INDEX

04 PowerSyntax connectors series

General features
Typical applications
Technical data
Technical features
Drain IP2X 

06 Chain Pilot

Technical data pilot microswitch
Panel source and panel drain
Panel circuits
Contacts
Overall dimensions

10 Chain Pilot Box

Product overview
Technical features
Technical data
Possible configurations
Overall dimensions

16 Basic panel or Shelter

Basic panel drain and source
Shelter panel connector
Panel mount cut-out options
Overall dimensions
Contacts and sleeve adapter system

22 PowerSyntax 45 | 90

Overall dimensions | Contacts

26 Line connectors

Short, standard and oversize body
Contacts and crimping data
Overall dimensions

33 Machined adaptors

34 Vertical PowerSyntax

Overall dimensions | Contact

37 Cable protection and management

38 Phase inverters / Adaptors

40 S2W 480 amp PowerSyntax

Multiplier | Adaptor | Phase inverter

42 InsuLugger

Part number | Overall dimensions

44 Premium Power Cables

Part number

46 SyntaxLock

48 Protection caps

50 Part Number explanation



PowerSyntax®

connectors series

PowerSyntax family of Powerlock-style single pole connectors.

The new PowerSyntax series of Powerlock compatible single pole connectors are specifically suited for the electrical supply management for currents up to 480amp or 750amp. Although fully intermateable with the original (and all the previous Syntax versions), the new PowerSyntax features a number of mechanical and technical enhancements which have been designed and incorporated to redefine the standards on this category of connectors as for safety, reliability, ease of handling and robustness in the harshest conditions.

General features

- Powerlock compatible
- Intermateable with other versions
- CE compliant
- EN/ESI compliant
- Contact retained within the thermoplastic housing with a flame-retardant UL94-VO plastic pin
- Quick assembling and disassembling, no special extracting tools are needed
- Heavy-duty ergonomic hand grip, with sides specifically designed for easy pushing/pulling when mating/unmating
- Metric thread M40 cable gland IP68 watertight compliant with EN/CE, adapters available for cables over 32 mm diameter
- Multipoint contact area
- Silver Plated Contacts
- Mechanically keyed to prevent mating errors
- High impact bodies
- Screw, Crimp and Lug terminals to facilitate cables from 25mm² to 300 mm²
- Permanent marking to identify phase/line and safety information embossed on connector's body























Typical applications

- Electrical power systems
- Power distribution
- Wind power
- Solar energy
- Battery units
- Mobile generators
- Industrial vehicles
- Railway installations
- Military installations
- Load banks
- Backup power systems
- Electrical power supply companies
- Heavy industry
- Outdoor concerts and sporting events
- Outdoor broadcasting
- Theatres

Technical data

- **Number of contacts:** single pole
- **Max continuous current rating with brass or bimetal contact:** 480amp
- **Max continuous current rating with copper contact:** 750amp
- **Operating Voltage:** 1.000V AC / 1.500V DC
- **Test Voltage:** 4.500 V AC
- **Short Circuit Rating:** 16,1kA (1 sec) 13,8kA (2sec) 11,5kA (3 sec) 35,5kA (peak)
- **Insulation Resistance:** >5.000 MOhm @500V
- **IP rating when mated:** IP67
- **Protection against electric shock:** IP2X
- **Contact resistance:** <0.1 mOhm
- **Housing material:** high temperature thermoplastic
- **Flammability:** UL94 V0


- **Coupling method:** bayonet lock with secondary locking pin
- **Number of mating cycles:** >500
- **Operating temperature:** -30°C/+125°C
- **Contact termination tightening torques:**
 - M12 threaded post 30Nm max
 - M12 threaded hole 30Nm max
 - ComLug L (480A) 30Nm max
 - ComLug L2 (750A) 30Nm max
 - ComLug XL (750A) 30Nm max
 - Set screw contact 12Nm max

	Ground	Neutral	Line 1	Line 2	Line 3
Europe & UK					
UK (old)					
Australia					
U.S.A.					

IP2X drain contact safety lock

Patented by Syntax

On our drain single pole connectors, the IP2X protection is obtained through a patented safety lock of the sharp-pointed insulated cap. This proprietary solution prevents pushing the contact inwards with fingers and provides mechanical lock in case of improper pushing of the contact.



PowerSyntax contact guide pin

For easy alignment of the holes on contact and insulating body, and quick insertion of the white dowel pin, the PowerSyntax contacts feature a guide pin with a corresponding recess in the insulator. After locating recess **A** in the body, find guide pin **B** on the contact, then insert guide pin **B** inside recess **A**, as shown in picture **C**. For contact fastening, after locating hole **D** on the body, insert dowel pin **E** in hole **D**. Contact retention is then completed (**F**).



Multilouver contact band and locking mechanism

To prevent a faulty retention of the contact band (1) and to ensure the efficiency of the connection, we adopted a solution which keeps the multilouver spring loaded band positively locked. The contact band is held in its locked position by a special ring, on which a 2.5 ton. pressure has been applied (2). This solution prevents derailment of the multilouver contact band (3).



Source contact IP2X threaded protection

The touch-proof protection on source contacts features a threaded attachment. A breakage of the insulation caps is a risk for the operators' safety. Thanks to this solution, the touch-proof cap is threaded and then blocked with specific adhesives. The bond between the protective elements and the live parts is strengthened, improving safety through a reduced exposure of the metal parts, as a portion of the cap will remain in position even in case of damage.



Chain pilot

Drain and source panel connectors
with **Microswitch**


The new CHAIN PILOT system is an evolution of the PowerSyntax panel-mount single pole connectors. VALENTINI - Syntax® has become the first manufacturer in the world to have developed and marketed powerlock-style panel-mount connectors with built-in microswitch (international patent). Now protective electrical interlocking and/or additional controls can now be obtained, allowing constant monitoring of all the conductors in a power circuit. When a Chain Pilot is mated, a spring device pressed by the line connector is operated, activating the pilot microswitch housed in the rear of the flange. The Chain Pilot connectors are suitable for currents up to 480amp or up to 750amp. They are fully intermateable with standard PowerSyntax or other powerlock-style connectors.

Technical data




Pilot microswitch

- Switching function: Changeover switch (spdt momentary)
- Number of poles: 1 - pole
- Connections: Quick-connect terminal, 2.8 x 0.5, sealed
- Mechanical life endurance: 10E6 Rating IEC / Rating North America 10 (3) a 250 v ac 10E3
- Design: DIN 41635 B
- Contact resistance (new condition): < 100 (1 A 12 V DC Mohm)
- Insulation resistance (new condition): > 100 (500 V DC) Mohm
- Voltage strength at 250V:
 - function insulation / basic insulation 1500 V
 - small contact distance 500 V
- Insulation spacing: acc. to EN 61058 for reinforced or double insulation
- Flammability: UL 94 V-0
- Glow wire test temperature: 850 °C



Activation button



Panel source

With microswitch


On the panel source, the spring device activating the microswitch is placed inside the mating part of the connector's shell.

Panel drain

With microswitch


On the panel drain, the spring device activating the microswitch is placed outside the mating part of the connector's shell.

Examples of connection applications



5 Panel drain circuit

5 PowerSyntax series panel drain connectors with built-in microswitches for phase conductors "L1, L2 & L3", neutral "N" and ground "E".



5 Panel source circuit

5 PowerSyntax series panel source connectors with built-in microswitches for phase conductors "L1, L2 & L3", neutral "N" and ground "E".

Contacts

The PowerSyntax Chain Pilot Panel connectors are equipped with different contact types, depending on current rating (480amp or 750amp) and cable terminations.



M12 threaded post

M12 threaded-post contact, up to 480 amp or 750 amp (all-copper contact). Lug terminal retained through M12 nut.



M12 threaded hole

M12 threaded-hole contact, up to 480 amp or 750 amp (all-copper contact). Lug terminal retained through M12 bolt.



Extended length contact M12 threaded post

M12 threaded-post contact, up to 480 amp or 750 amp (all-copper contact). Lug terminal retained through M12 nut.




Extended length contact M12 threaded hole


M12 threaded-hole contact, up to 480 amp or 750 amp (all-copper contact). Lug terminal retained through M12 nut.

Overall dimensions


Chain pilot panel connector




Panel drain
with M12 threaded post




Panel source
with M12 threaded post




Panel drain
with M12 threaded hole




Panel source
with M12 threaded hole




Panel drain
Extended length contact with M12 threaded post



Panel source
Extended length contact with M12 threaded post




Panel drain
Extended length contact with M12 threaded hole




Panel source
Extended length contact with M12 threaded hole

Panel mount cut-out dimensions



Panel drain front/rear



Panel source front/rear



Chain Pilot Box

The non-sequential safety box

The PowerSyntax Chain Pilot box features a set of PowerSyntax Chain Pilot connectors with L1+L2+L3+N+PE (or L1+L2+L3+PE), each one with its built-in microswitch. The connector's microswitches control an auxiliary circuit connected to an external device (breaker, contactor, etc.), so that the system will only be activated once all the mechanically keyed cable connectors have been inserted in the corresponding panel-mount connectors on the Chain Pilot Box. So there is no need to respect a sequential order when mating or unmating your connectors, unlike other Powerlock-compatible boxes.

All connectors will de-energise should one become disconnected when in use.

Product overview

- Insert all the cable connectors to activate the breaker or protection device
- All connectors will de-energise should one become disconnected when in use
- Built-in microswitch for electrical interlock on all connectors
- No mechanical locks / longer lifespan
- Ensures safe connection of all phases, neutral and earth
- Electrical safety guaranteed
- International patent on connectors

Supply notice

Environmental caps supplied as a standard to ensure IP67 even when connectors are unmated.



Chain Pilot panel connectors are patented by Syntax

Technical features

- Intermateable with standard PowerSyntax or other powerlock-style connectors
- Microswitch-controlled auxiliary circuit ensures that the system will only be energised when all 5 connectors on the box have been mated
- Total electrical safety as all connectors are de energised should one become disconnected
- Color coded connectors
- 5-pole (E-N-L1-L2-L3) or 4-pole (E-L1-L2-L3) system with Panel Drain or Source connectors
- Mechanically keyed connectors to prevent mating errors.
- Secondary lock for added mechanical safety
- IP2X finger-proof protection
- 2U 19" rack-mountable box
- IP67 rating on connectors' front mating side
- Microswitch-controlled auxiliary circuit ensures that the system will only be energised when all connectors on the box have been mated



Technical data

- Rated current: 480amp or 750amp
- Rated voltage: 1000V AC / 1500V DC
- Color coding:
 - EUROPE:** color coded connectors and panel inscriptions (E-green, N-blue, L1-brown, L2-black, L3-grey)
 - UK (old):** color coded connectors (E-green, N-black, L1-red, L2-yellow, L3-blue)
 - AUSTRALIA:** color coded connectors (E-green, N-black, L1-red, L2-white, L3-blue)
 - USA:** color coded connectors (E-green, N-white, L1-black, L2-red, L3-blue)
- Model: source or drain
- Contact material: silver plated copper

- Box material: high temperature thermoplastic
- Rack space: 2U or 2.5U
- Endurance: 500+ connection cycles
- Degree of protection (connectors front side): IP67 when mated of with environmental caps fitted (IP67 caps supplied as a standard)
- Degree of protection (connectors without caps): IP2X finger-proof
- Flammability: UL94 - V0
- Operating temperature: -30°C to +85°C

Safety notice

The PowerSyntax Chain Pilot Box should only be installed and operated by suitably qualified persons.




Choose between 128 configurations

Make your own Chain Pilot Box

Choose between a wide range of options: 4 or 5 poles, color coding by geographical region, source or drain connectors, up to 480A or up to 750A, 2U or 2,5U of box height and contact type, threaded post or threaded hole.


1. Choose your connector style

The PowerSyntax Chain Pilot connectors are available in Panel Drain e Panel Source versions.



Panel drain With microswitch

On the panel drain, the spring device activating the microswitch is placed outside the mating part of the connector's shell.



Panel source With microswitch

On the panel source, the spring device activating the microswitch is placed inside the mating part of the connector's shell.

2. Choose the number of poles

The Chain Pilot Box can be ordered with the standard 5-poles (G - N - L1 - L2 - L3) or in the 4-poles (G - L1 - L2 - L3) version.



5-poles version























4-poles version

















3. Choose the color coding

The PowerSyntax Chain Pilot connectors can be coded for Europe, UK (old), Australia and U.S.A. color schemes.

Identification color codes (5-POLES)

	Ground	Neutral	Line 1	Line 2	Line 3
Europe & UK					
UK (old)					
Australia					
U.S.A					

Identification color codes (4-POLES)

	Ground	Line 1	Line 2	Line 3
Europe & UK				
UK (old)				
Australia				
U.S.A				

4. Choose the contact's terminal

The PowerSyntax Chain Pilot panel connectors in the Chain Pilot Box are equipped with different contact types, depending on current rating (480amp or 750amp) and cable terminations.



Extended length contact M12 threaded post

M12 threaded-post contact, up to 480 amp or 750 amp (all-copper contact).
Lug terminal retained through M12 nut.




Extended length contact M12 threaded hole


M12 threaded-hole contact, up to 480 amp or 750 amp (all-copper contact).
Lug terminal retained through M12 bolt.

5. Choose the box height

Pick the right box for your rack, we can provide two options:
2U and 2.5U. Both choices are available for the 4-poles or the 5-poles versions.




Box height: 2U (89mm)



Box height: 2.5U (108mm)

Overall dimensions

Chain Pilot Box



Type	Poles	Units	Contact	A	B	C	D	E
Drain	4	2U	M12 post	89 mm	349,5 mm	57 mm	46 mm	161 mm
Drain	4	2U	M12 hole	89 mm	349,5 mm	57 mm	16,3 mm	131,3 mm
Drain	4	2.5U	M12 post	108 mm	349,5 mm	57 mm	46 mm	161 mm
Drain	4	2.5U	M12 hole	108 mm	349,5 mm	57 mm	16,3 mm	131,3 mm
Drain	5	2U	M12 post	89 mm	432 mm	57 mm	46 mm	161 mm
Drain	5	2U	M12 hole	89 mm	432 mm	57 mm	46 mm	161 mm
Drain	5	2.5U	M12 post	108 mm	432 mm	57 mm	46 mm	161 mm
Drain	5	2.5U	M12 hole	108 mm	432 mm	57 mm	16,3 mm	131,3 mm
Source	4	2U	M12 post	89 mm	349,5 mm	35 mm	46 mm	139 mm
Source	4	2U	M12 hole	89 mm	349,5 mm	35 mm	16,3 mm	109,3 mm
Source	4	2.5U	M12 post	108 mm	349,5 mm	35 mm	46 mm	139 mm
Source	4	2.5U	M12 hole	108 mm	349,5 mm	35 mm	16,3 mm	109,3 mm
Source	5	2U	M12 post	89 mm	432 mm	35 mm	46 mm	139 mm
Source	5	2U	M12 hole	89 mm	432 mm	35 mm	16,3 mm	109,3 mm
Source	5	2.5U	M12 post	108 mm	432 mm	35 mm	46 mm	139 mm
Source	5	2.5U	M12 hole	108 mm	432 mm	35 mm	16,3 mm	109,3 mm

Extra safety, even in the packaging

Every detail is important to us



We care about every aspect regarding the safety of our products, from the starting design to the final delivery. Every single Chain Pilot Box is enclosed in a polyethylene shell, inserted in a sealed cardboard package and shipped in another cardboard box, for further protection.



The IP67 caps are supplied as a standard

IP67 protection of the Chain Pilot Box is fully ensured when all the connectors are mated or all the environmental caps are fitted.





Basic panel or Shelter

Panel source, panel drain,
with threaded body and backshell

Discover our innovative, Powerlock compatible, single pole panel connectors: many options that will improve your productivity while bringing you peace of mind on all electrical insulation and safety-related issues. And no compromises on connectors' design and performances.

Basic panel connector

Panel Drain or Panel Source

Specific housing for protection cap lacing moulded on the plastic body of the flange. IP2X protection through patented drain contact lock and source finger protection to prevent touching live parts. Contact to housing retention through flame-retardant UL94-V0 plastic cotter pin. No special assembling tools needed. Secondary locking safety system. Front or rear panel mount. Optional M5 threaded fittings available for rear panel mount. Permanent phase / line identification and safety information markings embossed on connector's shell. No additional information stickers applied. SPX 4 480 amp and SPX 7 750 amp versions available. M12 contacts with M12 threaded post or M12 threaded hole. Other contact options available on request. For secondary lock release, use SyntaxLock or standard release key.



Panel drain
Front view



Panel drain
Rear view



Panel source
Front view



Panel source
Rear view


Shelter

Panel connector with threaded body and backshell


The PowerSyntax SPX panel-mount connectors are available with threaded body to fit two thermoplastic backshell variants, depending on the contact installed. As well as the backshells, this system features an IP68 cable gland and provides IP67 watertight seal at the cable clamp. The standard backshell version can be supplied with a set-screw contact terminal with reduction sleeves for 25-150 mm² copper cables up to 480 amp or crimp contacts for copper cables up to 300 mm² and currents up to 750 amp. The long backshell variant hosts our bimetal EasiLug contact, designed for aluminium cables.



Panel mount cut-out dimensions Basic panel and Shelter




Panel drain front/rear




Panel source front/rear

Overall dimensions


Basic panel and Shelter




Basic panel drain
with M12 threaded post




Basic panel source
with M12 threaded post




Basic panel drain
with M12 threaded hole




Basic panel source
with M12 threaded hole




Basic panel drain
with set screw contact




Basic panel source
with set screw contact




Basic panel drain
with crimp contact




Basic panel source
with crimp contact




Basic panel drain
with ComLug L




Basic panel source
with ComLug L




Basic panel drain
with ComLug L2




Basic panel source
with ComLug L2




Basic panel drain
with ComLug XL




Basic panel source
with ComLug L2




Basic panel drain
with EasiLug




Basic panel source
with EasiLug




Shelter panel drain
with standard backshell



Shelter panel source
with standard backshell



Shelter panel drain
with long backshell



Shelter panel source
with long backshell

Contacts

for Basic and Shelter panel connectors

The PowerSyntax Panel connectors are equipped with different contact types, depending on current rating (480 amp or 750 amp) and cable terminations.



M12 threaded post
for Basic panel

Up to 480 amp or 750 amp (all copper contact).
Lug terminal retained through M12 nut. Used as a standard on Basic panel-mount connectors.
Tightening torque 30Nm max.



M12 threaded hole
for Basic panel


Up to 480 amp or 750 amp (all copper contact). Lug terminal retained through M12 bolt. Used as an alternative for M12 threaded-post contacts on Basic panel-mount connectors. Tightening torque 30Nm max.



Crimp contact
for Basic panel and Shelter

Crimp contact, up to 750 amp, and up to 300 mm² cable sections. The position and number of cable compressions vary according to the different cable sections.
Cable stripping length is 42 mm.

For all crimping data see the section starting from page 30




SPY ComLug L
for Basic panel

Entirely designed and produced by Syntax, contact up to 480 amp.
Depending on the model, they can be suitable for lug terminals up to 120 mm². Tightening torque 30Nm max.



SPY ComLug L2
for Basic panel

Entirely designed and produced by Syntax, contact up to 750 amp and suitable for lug terminals up to 240 mm² of cable section. Tightening torque 30Nm max.



SPY ComLug XL
for Basic panel

Entirely designed and produced by Syntax, contact up to 750 amp and suitable for lug terminals up to 300 mm² of cable section. Tightening torque 30Nm max.

Set screw contact for Basic panel and Shelter

Up to 480 amp. Cable retained through reduction sleeve (25-150 mm²) and set screws suitable reduction sleeve is included. Used as a standard on SPX/SPZ 480 amp line source/drain connectors, the set screw contact is also available for panel connectors on request. Tightening torque 12Nm max.



Sleeve adapter system for set screw contacts

The ultimate solution for 25 to 95 mm² cables.

On other connectors on the market, multiple concentric sleeves are used to reduce the cable section from 150 or 120 mm² down to the smaller section specifically needed. The thoughtful design and the mechanical reliability of the our sleeve adapter eliminates the need to use multiple concentric sleeves.

Cable section (class 5)	25 mm ²	35 mm ²	50 mm ²	70 mm ²	95 mm ²	120 mm ²	150 mm ²
Recommended sleeve adapter (p/n)	SPX-RED025	SPX-RED035	SPX-RED050	SPX-RED070	SPX-RED095	-	-
Cable strip length	33 mm	33 mm	33 mm	33 mm	33 mm	33 mm	33 mm
Set screw tightening torque	12Nm	12Nm	12Nm	12Nm	12Nm	12Nm	12Nm
M10 hex set screw (2pcs)	allen key size 5	allen key size 5	allen key size 5	allen key size 5	allen key size 5	allen key size 5	allen key size 5

Contacts for aluminium cables for currents up to 480 amp



SPY EasiLug - Bimetal for Basic panel and Shelter

Complete EasiLug contact with bi-metal (aluminium/copper terminal) for aluminium cables. Used as a standard on SPY EasiLug line connectors for aluminium cables, this contact type is also available for panel-mount connectors on request.

For all crimping data see the section starting from page 30



PowerSyntax 45 PowerSyntax 90

Single pole 45 or 90 degree
angled panel connectors

PowerSyntax 45 and PowerSyntax 90 are designed to provide space saving options for your operations and a better management of your single pole, Powerlock compatible, panel-mount connections. Thanks to their versatile design they are an ideal combo with our patented Chain Pilot models, with our Basic panel connectors as a further option. PowerSyntax 45 and PowerSyntax 90 are available for current ratings up to 480 amp or 750 amp, Source and Drain versions.

PowerSyntax 45

Drain and Source | 480 or 750 amp

Extra grip on plastic materials thanks to A2 stainless steel screws with pan heads. Knurled brass threaded inserts providing secure fixing to panels. IP2X protection through patented drain contact lock. Secondary locking safety system. Permanent phase identification and safety information markings engraved on connector's body. No stickers applied.



PowerSyntax 90


Drain and Source | 480 or 750 amp

Extra grip on plastic materials thanks to A2 stainless steel screws with pan heads. Knurled brass threaded inserts providing secure fixing to panels. IP2X protection through patented drain contact lock. Secondary locking safety system. Permanent phase identification and safety information markings engraved on connector's body. No stickers applied.




Overall dimensions

PowerSyntax 45



Panel drain

Side view




Panel source

Side view

Panel mount cut-out dimensions

PowerSyntax 45



Panel drain/source

Contact

for PowerSyntax 45




M12 threaded hole

Standard contact
for PowerSyntax 45

Up to 480 amp or 750 amp (all
copper contact). Lug terminal
retained through M12 bolt.
Tightening torque 30Nm max.


Overall dimensions

PowerSyntax 90



Panel drain

Side view




Panel source

Side view

Panel mount cut-out dimensions

PowerSyntax 90



Panel drain/source

Contact

for PowerSyntax 90

M12 threaded post

Standard contact
for PowerSyntax 90



Up to 480 amp or 750 amp (all copper contact). Lug terminal retained through M12 nut.
Tightening torque 30Nm max.



Line connectors

Line source and Line drain
480 and 750 amp

A full range of high current, Powerlock compatible, single pole connectors for your cables. With 3 different shell versions and 7 contact types, an unprecedented range of combinations is made available for you. No matter the section of your cables, in the PowerSyntax range you are sure to find YOUR ideal solution to manage any sections from 25 to 300 mm². For copper or aluminium cables, with no compromises on connectors' design and performances.

Short body connector

Line drain and line source | 480 amp

Innovative ergonomic hand grip for easy handling. IP2X protection through patented drain contact lock and source finger protection to prevent touching live parts. Contact to housing retention through flame-retardant UL94-VO plastic cotter pin. No special assembling tools needed. Secondary locking safety system. IP68 watertight M40 plastic cable gland for cable strain relief, with 15 - 32 mm clamping range. Permanent phase/line identification and safety information markings embossed on connector's shell. No additional information stickers applied.



Line drain
Short body connector



Line source
Short body connector

Standard body connector

Line drain and line source 480 amp & 750 amp

Innovative ergonomic hand grip for easy handling. IP2X protection through patented drain contact lock and source finger protection to prevent touching live parts. Contact to housing retention through flame-retardant UL94-VO plastic cotter pin. No special assembling tools needed. Secondary locking safety system. IP68 plastic cable gland for cable strain relief, with 15 - 32 mm (M40) or 30 - 38 mm (M50) clamping range. Permanent phase/line identification and safety information markings embossed on connector's shell. No additional information stickers applied.



Line drain
Standard body connector



Line source
Standard body connector

Oversized body connector

Line drain and line source | 750 amp

Extra large body cavity, ideal when using lug terminals for big cable sections. Improved hand grip for easy handling. IP2X protection through patented drain contact lock and source finger protection to prevent touching live parts. Contact to housing retention through flame-retardant UL94-VO plastic cotter pin. No special assembling tools needed. Secondary locking safety system. IP68 plastic cable gland for cable strain relief, with 30 - 38 mm (M50) clamping range. Permanent phase/line identification and safety information markings embossed on connector's shell. No additional information stickers applied.



Line drain
Oversized body connector



Line source
Oversized body connector

Contacts

and cable retention types for line connectors

The PowerSyntax connectors are equipped with different contact types, depending on current rating (480 amp or 750 amp), cable material (aluminum or copper), connectors body type (line or panel-mount) and cable terminations.

Solutions for copper cables



Set screw contact

Up to 480 amp. Cable retained through reduction sleeve (25-150 mm²) and set screws suitable reduction sleeve is included. Used as a standard on SPX/SPZ 480 amp line source/drain connectors, the set screw contact is also available for panel-mount connectors on request. Tightening torque 12Nm max.

Sleeve adapter system for set screw contacts

The ultimate solution for 25 to 95 mm² cables.
On other connectors on the market, multiple concentric sleeves are used to reduce the cable section from 150 or 120 mm² down to the smaller section specifically needed. The thoughtful design and the mechanical reliability of the our sleeve adapter eliminates the need to use multiple concentric sleeves.



Cable section (class 5)	25 mm ²	35 mm ²	50 mm ²	70 mm ²	95 mm ²	120 mm ²	150 mm ²
Recommended sleeve adapter (p/n)	SPX-RED025	SPX-RED035	SPX-RED050	SPX-RED070	SPX-RED095	-	-
Cable strip length	33 mm	33 mm	33 mm	33 mm	33 mm	33 mm	33 mm
Set screw tightening torque	12Nm	12Nm	12Nm	12Nm	12Nm	12Nm	12Nm
M10 hex set screw (2pcs)	allen key size 5	allen key size 5	allen key size 5	allen key size 5	allen key size 5	allen key size 5	allen key size 5



Crimp contact for standard body connector

Crimp contacts, up to 750 amp, and up to up to 300 mm² cable sections. The position and number of cable compressions will vary according to the different cable sections. Cable stripping length is 42 mm.

For all crimping data see the section starting from page 30



Lug converters for copper cables terminated with common lugs



SPY ComLug L
Lug Converter




For standard body connector
Entirely designed and produced by Syntax, contact up to 480 amp. Depending on the model, they can be suitable for lug terminals up to 120 mm². Tightening torque 30Nm max.



SPY ComLug L2
Lug Converter




For oversized body connector
Entirely designed and produced by Syntax, contact up to 750 amp and suitable for lug terminals up to 240 mm² of cable section. Tightening torque 30Nm max.



SPY ComLug XL
Lug Converter



For oversized body connector
Entirely designed and produced by Syntax, contact up to 750 amp and suitable for lug terminals up to 300 mm² of cable section. Tightening torque 30Nm max.



Lug Type	B	Cable section (flex)	Øi	d Ø screw	Contact
S	25,0	70 - 95 mm ²	13,5	12 mm	L - L2 - XL
S	28,5	95 - 120 mm ²	15,2	12 mm	L - L2 - XL
S	31,5	120 - 150 mm ²	16,7	12 mm	L2 - XL
S	35,5	150 - 185 mm ²	19,2	12 mm	L2 - XL
C	31,0	240 mm ²	21,1	12 mm	L2 - XL
C	31,0	300 mm ²	23,7	12 mm	XL

Solutions for aluminium cables for currents up to 480 amp



SPY EasiLug - Bimetal

Complete EasiLug contact with bi-metal (aluminium/copper terminal) for aluminium cable. Used as a standard on SPY EasiLug connectors for aluminium cables, this contact type is also available for panel-mount connectors on request.

For all crimping data see the section starting from page 30



SPV - Bimetal


Bimetal (aluminium/copper) crimp contact for up to 300 mm² cable sections. Designed to be used in combination with aluminium cables.

For all crimping data see the section starting from page 30

Crimping data

and cable stripping



On crimp contacts (up to 750 amp copper / 480 amp bimetal, and up to up to 300 mm² cable sections), the position and number of cable compressions will vary according to the different cable sections (see tables below).



Aluminium cables - SPY EasiLug

Class 5

Lug model	120 mm ²	150 mm ²	185 mm ²	240 mm ²	300 mm ²
Contact internal Ø	15 mm	16,5 mm	18,5 mm	21,3 mm	23,3 mm
Cable strip length (L)	60 mm	60 mm	60 mm	60 mm	60 mm
No. of crimpings	3	3	3	3	3
Crimping width	14 mm	14 mm	14 mm	14 mm	14 mm
Crimp die set p/n	SBH-CRIMP-120AL	SBH-CRIMP-150AL	SBH-CRIMP-185AL	SBH-CRIMP-240AL	SBH-CRIMP-300AL



Crimp in the middle of each crimping area, inside the guides.

Aluminium cables - SPV

Class 5



Lug model	120 mm ²	150 mm ²	185 mm ²	240 mm ²	300 mm ²
Contact internal Ø	15 mm	16,5 mm	18,5 mm	21,3 mm	23,3 mm
Cable strip length (L)	42 mm	42 mm	42 mm	42 mm	42 mm
No. of crimpings	2	2	2	2	2
Crimping width	14 mm	14 mm	14 mm	14 mm	14 mm
Crimp die set p/n	SBH-CRIMP-120AL	SBH-CRIMP-150AL	SBH-CRIMP-185AL	SBH-CRIMP-240AL	SBH-CRIMP-300AL


Crimp in the middle of each crimping area, inside the guides.



Copper cables - SPX

Class 5

Contact model source/drain	150/185 mm ²	185/240 mm ²	240/300 mm ²	300 mm ²
Contact internal Ø	17,9 mm	19,7 mm	22,2 mm	23,7 mm
Cable strip length (L)	42 mm	42 mm	42 mm	42 mm
No. of crimpings	2	2	3	3
Crimping width	14 mm	14 mm	7 mm	7 mm
Crimp die set p/n	SBH-CRIMP- 185/240RM	SBH-CRIMP- 185/240RM	SBH-CRIMP- 240/300RM	SBH-CRIMP- 240/300RM



Crimp in the middle of each crimping area, inside the guides.

Hydraulic crimp tool

Hand operated or cordless



Hand operated hydraulic crimp tool

Part No. **SBH-CRIMP-B**



Cordless hydraulic crimp tool

Part No. **SBH-CRIMP-C**



Alumnium

Crimp die set for hydraulic crimp tools

For corresponding part numbers
see the table in the previous page



Copper

Crimp die set for hydraulic crimp tools

For corresponding part numbers
see the table above.


Overall dimensions

Line version



Short body

Line drain | Actual product




Short body

Line drain | Dimensions



Short body

Line source | Actual product




Short body

Line source | Dimensions



Standard body

Line drain | Actual product




Standard body

Line drain | Dimensions



Standard body

Line source | Actual product




Standard body

Line source | Dimensions



Oversized body

Line drain | Actual product




Oversized body

Line drain | Dimensions



Oversized body

Line source | Actual product



Oversized body

Line source | Dimensions

Machined adaptors

for PowerSyntax line connectors

Adaptors and extensions thoughtfully designed and built to widen the clamping range options of your PowerSyntax connectors.




Extra quality in every detail

Our accessories are the state of the art not only in terms of design but also for the properties of the material employed. The Acetal resin, commonly known as POM-C, is characterized by high mechanical strength, stiffness, heat resistance, good antifriction properties, low moist absorption and high resistance to a wide range of chemicals, including many solvents. Every piece is individually machined from a single block of solid plastic.


M40 to M50 adaptor


for PowerSyntax connectors and M50 cable glands



M40 to M40 backshell extension

for Standard body connectors with EasiLug contacts





Vertical PowerSyntax

Single pole 90 degree angled cable connector

Finally a PowerSyntax 90 degrees angled single pole cable connector, designed and built with great attention to every detail, like we always do. Every piece is carefully machined in our mechanical workshop, to ensure the maximum reliability and safety for the operator. Vertical PowerSyntax is built to carry currents up to 480 or 750 amp. Available in source and drain versions and in all regional conductor/color combinations.

Bending the rules of connection

The easiest way to save space

A new way to imagine single pole cable connectors, the new Vertical PowerSyntax is the ideal solution when space saving is key. Vertical is a right-angled cable connector, fitted with a M12 threaded hole contact for currents up to 480 or 750 amp.

IP2X protection through patented drain contact lock. Secondary locking safety system. M40 cable glands, available with 3 different clamping range options. Permanent phase identification and safety information markings engraved on connector's body. No stickers applied. Drain and Source versions available.

Contact us for more information and ordering details.



Line drain

Vertical PowerSyntax
480 | 750 amp




Line source

Vertical PowerSyntax
480 | 750 amp




Overall dimensions


Vertical PowerSyntax




Vertical PowerSyntax
Line drain | Dimensions
Side view



Vertical PowerSyntax
Line drain | Dimensions
Front view



Vertical PowerSyntax
Line source | Dimensions
Side view



Vertical PowerSyntax
Line source | Dimensions
Front view

Contact

for Vertical PowerSyntax



M10 threaded hole

Standard contact

Up to 750 amp, all copper contact.
Lug terminal retained through M10 bolt.

Cable protection and management

Wire mesh strain reliefs, hanger grips and pulling grips

Explore our full range of wire mesh solutions designed to be fitted on cables or directly on PowerSyntax connectors for optimal cable management, increased protection and longer life span.



For a perfect connection you'll need more than a great connector

Discover our cable management solutions

The quality of a connection depends on many factors. Reliable connectors are essential, of course, and the cables are a top priority too. Choosign high quality products made with the best materials is important, but there are other parts of the job that should not be overlooked. How you lay a cable, how you protect it from unwanted stresses, how you make sure it will be safeguarded from external elements that might possibly damage your connections over time, these decisions are all integral to achieve highly reliable connections.

Our accessories are thoughtfully designed and manufactured for ideal cable management, handling and protection.

Strain Reliefs

Thoughtfully designed to reduce tension on cables and, therefore, stress related damages to your connections due to excessive bending. Available in a wide range of thread sizes and overall diameters to fit any connector and cable combinations.

Hanger grips

Heavy duty wire mesh hangers are designed to ensure optimal support and right retention of the cable without any sliding or scraping of the external jacket. Different styles and sizes are available in stock for any kind of application, both indoors or outdoors.

Pulling grips

Created to provide the operators an efficient way to pull cables through ducts or other spaces in the safest possible way. Made to be extremely resistant and conveniently reusable, and fit to a large number of applications. Different models available.





Phase Inverters / Adaptors

**Fast, safe and reliable reversal
of two phase conductors.**

Discover the whole range of PowerSyntax Inverters/Adaptors, available for currents up to 480 or up to 750 amp and in every combination of phases and regional color coding. Check the tables in the next page and compose the part number of the model you need.

Say goodbye to uncomfortable last minute adaptors on cable

The PowerSyntax® Phase Inverters/Adaptors, available for electric currents up to 480 amp and now also up to 750 amp, have been designed to solve two specific problems: first, reverse the rotation direction in three phase motors by changing the phase sequence (L1-L2-L3) between the power source and the connected devices; second, provide those who use only one model of phase conductor (L1, L2 or L3) to operate L1-L2-L3+Neutral systems with an interface between standard 3-phase power generators and distros and their devices. The former is a common demand in industrial applications. The latter is a specific need of entertainment and cinema industries.



480 amp available version and p/n

IN male	EU	UK	AU	US	OUT female	EU	UK	AU	US	Part Number
L1	■	■	■	■	L2	■	■	■	■	SPZ4LD1__ - LS2__
L1	■	■	■	■	L3	■	■	■	■	SPZ4LD1__ - LS3__
L2	■	■	■	■	L1	■	■	■	■	SPZ4LD2__ - LS1__
L2	■	■	■	■	L3	■	■	■	■	SPZ4LD2__ - LS3__
L3	■	■	■	■	L1	■	■	■	■	SPZ4LD3__ - LS1__
L3	■	■	■	■	L2	■	■	■	■	SPZ4LD3__ - LS2__

750 amp available version and p/n

IN male	EU	UK	AU	US	OUT female	EU	UK	AU	US	Part Number
L1	■	■	■	■	L2	■	■	■	■	SPZ7LD1__ - LS2__
L1	■	■	■	■	L3	■	■	■	■	SPZ7LD1__ - LS3__
L2	■	■	■	■	L1	■	■	■	■	SPZ7LD2__ - LS1__
L2	■	■	■	■	L3	■	■	■	■	SPZ7LD2__ - LS3__
L3	■	■	■	■	L1	■	■	■	■	SPZ7LD3__ - LS1__
L3	■	■	■	■	L2	■	■	■	■	SPZ7LD3__ - LS2__

Compose the part number of the model you need by inserting the regional codes in the blanks in the tables below.



L3 - L2



L3 - L1



L2 - L3



L2 - L1



L1 - L3



L1 - L2



PowerSyntax S2W 480 amp

Multiplier | Adaptor | Phase inverter

Available with EU, UK, AUS and USA color coding.

A complete range of PowerSyntax multipliers, adaptors and phase inverters for currents up to 480 amp, available in standard or reverse versions and with multicolor coding options.



S2W 480 amp multiplier

S2W with 1 drain input and 2 source outputs PowerSyntax 480 amp connectors. Available with EU, UK, AUS and USA color coding. Standard and reverse versions are available. On the reverse version, the input is inline with one of the outputs.

Example p/n - EU color coding

1 input male	color	2 output female	color	Part Number
Line 1	Orange	Line 1	Orange	S2WX111000S
Line 2	Black	Line 2	Black	S2WX222000S
Line 3	Grey	Line 3	Grey	S2WX333000S
Neutral	Blue	Neutral	Blue	S2WXNNN000S
Ground	Green	Ground	Green	S2WXGGG000S

Notice:

- for the reverse version replace final "S" by "R" in the Part Number
- for the version with safety lacing add "-L" at the end of the Part Number
- IP67 or IP53 protection caps available on request.

Typical applications

- All temporary electrical systems
- Power distribution
- Outdoor concerts and sports events
- Outdoor broadcasting
- Theaters, studios and film sets
- Mobile generators
- Industrial vehicles
- Railway and military installations
- Load banks
- Back-up power systems

S2W 480 amp phase inverters/adaptors

The PowerSyntax Phase Inverters/Adaptors have been designed to solve two specific problems: first, reverse the rotation direction in 3-phase motors, etc. by changing the phase sequence (L1-L2-L3) between the power source and the connected devices, a common demand in industrial applications; second, provide those who use only one model of phase conductor (L1, L2 or L3) to operate L1-L2-L3+Neutral systems with an interface between standard three-phase power generators/distros and their devices a typical need in the entertainment industry. Standard and reverse versions are available. On the reverse version, the input is inline with one of the outputs.


Example p/n - EU color coding

1 input male	color	2 output female	color	Part Number
Line 1	Orange	Line 3	Grey	S2WX133000S
Line 2	Black	Line 3	Grey	S2WX233000S
Line 3	Grey	Line 2	Black	S2WX322000S
Line 1	Orange	Line 2	Black	S2WX122000S
Line 2	Black	Line 1	Orange	S2WX211000S
Line 3	Grey	Line 1	Orange	S2WX311000S

Notice:

- for the reverse version replace final "S" by "R" in the Part Number
- for the version with safety lacing add "-L" at the end of the Part Number
- IP67 or IP53 protection caps available on request.





**NEW
2023**



InsuLugger

Smart and safe protective joint
for lug terminated power cables

InsuLugger is designed to create an incredibly steady, weatherproof single pole connection, and to make it last for all the time you need. To make its shells, we chose a plastic material with unique qualities: the Acetal resin, commonly known as POM-C and characterized by high mechanical strength, stiffness, heat resistance and good antifriction properties. InsuLugger provides total protection against dust, and is IP68 rated to withstand permanent immersion in water. To avoid improper tampering with connections, our R&D department studied a new safety measure, a blocking screw that the operator has to loosen in order to be able to release the secondary locking system.



InsuLugger Wide

Suitable for 240 and 300 mm² cables

Part number: **SPL-WIDE-MU**

Cable glands: M50 Oversize - Clamping range 30-38mm


Characteristics

Mechanically, thermally, electrically impressive **resin** with a great resistance to water.

IP68 rated: total protection against dust and safe permanent immersion.

Secondary locking system with dedicated ergonomic release key, that allows a safe and convenient way to access the lugs joint core.

Blocking screw that the operator has to loosen in order to be able to release the secondary locking system.



Practical set of **color coded disks** to recognize your connection's phase.



InsuLugger Slim

Suitable for 120, 150 & 185 mm² cables

Part number: **SPL-SLIM-MQ**

Cable glands: M40 Reduced - Clamping range 15-23mm

Part number: **SPL-SLIM-MP**


Cable glands: M40 Normal - Clamping range 19-28mm

Part number: **SPL-SLIM-MR**

Cable glands: M40 Oversize - Clamping range 22-32mm




Overall dimensions




InsuLugger Slim

Side view



InsuLugger Wide

Side view



Premium Power Cables

Assembled by our specialists
Ready to use right away

Pre-made cable extension with all the reliability of PowerSyntax connectors, only the best cables for great performances and the unmatched comfort of our pulling grips, supplied as standard with each cable. A ready-made solution, in compliance with the international safety regulation.

Choose directly from our stock

Available lengths: 5-10-20-30-50 m

Choose phase/conductor and color

Heavy-duty extra flexible H07RN-F rubber cable with conductive 120mm² single copper core, rubber insulation and neoprene sheath. Oil-resistant and flame-retardant. Every cable is provided with 2x transparent heat shrink for additional marking at customer's care. 5 m cables are provided with 1 pulling grip (drain connector's side). 10, 20, 30, 50 m cables are provided with 2 pulling grips (1 at each connector's side).






Do you need a different combination?

Let's shape your Premium Power Cable together!

Perhaps you couldn't find your ideal extension cable version in our stock? Maybe you need a different phase/color or cable length? Please contact us as our specialists are ready to build it for you.





Example p/n - EU color coding

	Ground	Neutral	Line 1	Line 2	Line 3	All phases (5 cables)
Length						
05 m	SPXE05GN	SPXN05BL	SPX105BR	SPX205BK	SPX305GY	SPX505EU
10 m	SPXE10GN	SPXN10BL	SPX110BR	SPX210BK	SPX310GY	SPX510EU
20 m	SPXE20GN	SPXN20BL	SPX120BR	SPX220BK	SPX320GY	SPX520EU
30 m	SPXE30GN	SPXN30BL	SPX130BR	SPX230BK	SPX330GY	SPX530EU
50 m	SPXE50GN	SPXN50BL	SPX150BR	SPX250BK	SPX350GY	SPX550EU

Used to dragging your cables by pulling the connector? Forget it!

Our PowerSyntax Line connectors are so ergonomic, we know. But using them to pull the cable can be dangerous. That's why our heavy duty pulling grips are always included, for you to comfortably pull the cable from the handle and not from the connector. This prevents damaging cable-to-connector joints and guarantees maximum safety for the operators.





SyntaxLock

Release system

Forgot to take some release keys with you before heading to work? Now you can unlock your connectors with SyntaxLock. A simple, universal accessory, quick and easy to install, suitable for all PowerSyntax connectors. SyntaxLock can be fitted or removed at any time.

Now you are free to forget the keys

SyntaxLock is a proprietary release system for the secondary lock on PowerSyntax connectors and IP67 protection caps. A simple yet powerful add-on to your connectors, SyntaxLock combines faster, more practical unlocking with complete safety. In fact it is very easy to install and to use but, in full compliance with the international electrical regulations, unmating still needs a voluntary operation on the key. SyntaxLock is supplied as a separate accessory and can be used for the retrofit of all PowerSyntax connectors built as of 2011.

CAUTION: SyntaxLock must be operated only by qualified technicians in safe and controlled work environments. Do not unclouple under load.



Aiming to the future with an eye on the past

Upgrade the equipment you already own. SyntaxLock is provided as a separate kit and can be used to retrofit every source connector, line or panel, or every IP67 protection cap produced by Syntax since 2011. There is no need to change your equipment to enjoy the improved ease of use of SyntaxLock, just install it on your own PowerSyntax connectors or IP67 protection caps.

A kit for every need

The SyntaxLock is supplied as a universal kit to be fitted on line source or panel source connectors and on IP67 protection caps for drain line and panel connectors. The kit consists of a universal collar, one release key for a panel source connector, one release key for either a line source connector or a IP67 protection cap for drain connectors, one nut and bolt set.

Part Number: **SPX-SYLOCK**



Panel
SyntaxLock
for panel source



Line
SyntaxLock
for line source



Caps
SyntaxLock
with IP67 protection caps



Protection caps

IP67 and IP53 versions available

A full range of protective covers to prevent damages when your connectors are unmated. PowerSyntax IP67 caps ensure complete waterproof protection while IP53 caps are a fast and easy way to protect connectors.



IP67 Protection caps

The PowerSyntax IP67 caps ensure complete waterproof protection

The PowerSyntax caps are universally keyed to be fitted on any connector's phase, so that just one cap version is needed respectively for Source and Drain connectors resulting in easier management and lower investment through reduced stock assortment. For full safety, the PowerSyntax IP67 caps feature the secondary locking system. The secondary lock will be released using SyntaxLock or a standard release key.



IP67 protective cover for drain

with special housing on caps for lacing

Part Number: **SPXDCCD-SC-IP67**



IP67 protective cover for source

with special housing on caps for lacing

Part Number: **SPXDCCS-SC-IP67**



Protection caps lacing

On the PowerSyntax caps, all details have been designed with a strong focus on resistance and reliability. A specific housing for the cap's lacing has been moulded directly on the flange of the panel-mount versions and on the body of the inline versions. The caps are laced to the connector's body through a special high-resistance cable made up of seven stainless strands, and covered by anti-scratch teflon black tubing.

IP53 Protection caps

The IP53 caps are fast, easy way to protect PowerSyntax connectors

The use of protective caps results in:

- Extended life span of the connectors as the mating faces are protected against impact damage and abrasion.
- Improved safety as contacts are protected against dust and water even when the connectors are not mated.



IP53 protective cover for drain

with special housing on caps for lacing

Part Number: **SPXDCCD-SC**



IP53 protective cover for source

with special housing on caps for lacing


Part Number: **SPXDCCS-SC**

PART NUMBER EXPLANATION

PowerSyntax Line connectors version short and standard

Example Part Number

SPX 4 LD E GN 025 MQ



Connector Series

SPX Standard body

SPZ Short body

Maximum Current Rating

4 Up to 480amp (25 to 150mm²)

7 Up to 750amp (185 to 300mm²)

- Crimp contact also available from 25 to 150mm² on request

Connector Style

LD Line Drain

LS Line Source

Key Composition

E Earth

N Neutral

1 Phase 1

2 Phase 2

3 Phase 3

Insulator Color

GN Green

BL Blue

BR Brown

BK Black

GY Gray

RD Red

YE Yellow

WH White

Contact Versions

Set-screw contact

025 25 mm²

035 35 mm²

050 50 mm²

070 70 mm²

095 95 mm²

120 120 mm²

150 150 mm²

Crimp contact (only SPX series)

165 120/150 mm² | internal Ø 16,5 mm | No. of crimpings 2

179 150/185 mm² | internal Ø 17,9 mm | No. of crimpings 2

197 185/240 mm² | internal Ø 19,7 mm | No. of crimpings 2

222 240/300 mm² | internal Ø 22,2 mm | No. of crimpings 3

237 300 mm² | internal Ø 23,7 mm | No. of crimpings 3

Cable Gland

MQ Reduced M40 gland Ø 15-23 mm

MP Normal M40 gland Ø 19-28 mm

MR Oversized M40 gland Ø 22-32 mm

MU M50 gland Ø 30-38 mm

Special Versions

Compatible accessories to be ordered separately

SPX-SYLOCK SyntaxLock quick secondary lock release system

SPXTKEY Secondary lock release key

SPXDSCS-SC IP53 Protective plastic cap kit for source connectors

SPXDSCD-SC IP53 Protective plastic cap kit for drain connectors

SPXDSCS-SC-IP67 IP67 protection cap for source connectors

SPXDSCD-SC-IP67 IP67 protection cap for drain connectors

SPX-RED025 Sleeve adapter for 25mm² set-screw contact

SPX-RED035 Sleeve adapter for 35mm² set-screw contact

SPX-RED050 Sleeve adapter for 50mm² set-screw contact

SPX-RED070 Sleeve adapter for 70mm² set-screw contact


SPX-RED095 Sleeve adapter for 95mm² set-screw contact

PART NUMBER EXPLANATION

PowerSyntax panel connectors

Example Part Number

SPX 4 PD E GN 150 MQ T5



Connector Series

SPX Standard version

Maximum Current Rating

4 Up to 480amp (25 to 150mm²)
7 Up to 750amp (185 to 300mm²)

Connector Style

PD Panel Drain
PS Panel Source

Key Composition

E Earth
N Neutral
1 Phase 1
2 Phase 2
3 Phase 3

Insulator Color

GN Green 
BL Blue 
BR Brown 
BK Black 
GY Gray 
RD Red 
YE Yellow 
WH White 

Contact Versions

M02 Threaded M12 hole
M12 Threaded M12 post

Set-screw contact

025 25 mm²
035 35 mm²
050 50 mm²
070 70 mm²
095 95 mm²
120 120 mm²
150 150 mm²

Crimp contact

165 120/150 mm² | internal Ø 16,5 mm | No. of crimpings 2
179 150/185 mm² | internal Ø 17,9 mm | No. of crimpings 2
197 185/240 mm² | internal Ø 19,7 mm | No. of crimpings 2
222 240/300 mm² | internal Ø 22,2 mm | No. of crimpings 3
237 300 mm² | internal Ø 23,7 mm | No. of crimpings 3

SHELTER Special Versions with backshell

00 Connector body without backshell thread
M0 Backshell without cable gland
MQ Threaded body with backshell and reduced M40 gland Ø 15-23 mm
MP Threaded body with backshell and normal M40 gland Ø 19-28 mm
MR Threaded body with backshell and oversized M40 gland Ø 22-32 mm
MU Threaded body with backshell, M40-M50 adaptor M50 gland Ø 30-38 mm (please contact us for more information about the sizes)

Special Versions

00 No special version
T5 Brass M5 threaded inserts (4 inserts applied to the connector)
NF No flange

Compatible accessories to be ordered separately

SPX-SYLOCK SyntaxLock quick secondary lock release system
SPXTKEY Secondary lock release key

SPXDSC-SC IP53 Protective plastic cap kit for source connectors
SPXDSD-SC IP53 Protective plastic cap kit for drain connectors
SPXDSC-SC-IP67 IP67 protection cap for source connectors
SPXDSD-SC-IP67 IP67 protection cap for drain connectors

SPX-RED025 Sleeve adapter for 25mm² set-screw contact
SPX-RED035 Sleeve adapter for 35mm² set-screw contact
SPX-RED050 Sleeve adapter for 50mm² set-screw contact
SPX-RED070 Sleeve adapter for 70mm² set-screw contact
SPX-RED095 Sleeve adapter for 95mm² set-screw contact


PART NUMBER EXPLANATION

PowerSyntax Chain Pilot connectors with microswitch



Example Part Number

SCP 4 PD E GN 150 00T5



Connector Series

SCP Chain Pilot version

Maximum Current Rating

4 Up to 480amp (25 to 150mm²)
7 Up to 750amp (185 to 300mm²)

Connector Style

PD Panel Drain
PS Panel Source

Key Composition

E Earth
N Neutral
1 Phase 1
2 Phase 2
3 Phase 3

Insulator Color

GN Green
BL Blue
BR Brown
BK Black
GY Gray
RD Red
YE Yellow
WH White

Contact Versions

M02 Threaded M12 hole
M12 Threaded M12 post
M22 Extended length contact with threaded M12 hole
M32 Extended length contact with threaded M12 post

Set-screw contacts (Available on request)

025 25 mm² Set-screw contact
035 35 mm² Set-screw contact
050 50 mm² Set-screw contact
070 70 mm² Set-screw contact
095 95 mm² Set-screw contact
120 120 mm² Set-screw contact
150 150 mm² Set-screw contact

Crimp contacts (Available on request)

165 120/150 mm² | internal Ø 16,5 mm | No. of crimpings 2
179 150/185 mm² | internal Ø 17,9 mm | No. of crimpings 2
197 185/240 mm² | internal Ø 19,7 mm | No. of crimpings 2
222 240/300 mm² | internal Ø 22,2 mm | No. of crimpings 3
237 300 mm² | internal Ø 23,7 mm | No. of crimpings 3

Special Versions

00T5 Brass M5 threaded inserts
 (4 inserts applied to the connector)

Compatible accessories to be ordered separately

SPX-SYLOCK SyntaxLock quick secondary lock release system
SPXTKEY Secondary lock release key

SPXDCS-SC IP53 Protective plastic cap kit for source connectors
SPXDCD-SC IP53 Protective plastic cap kit for drain connectors
SPXDCS-SC-IP67 IP67 protection cap for source connectors
SPXDCD-SC-IP67 IP67 protection cap for drain connectors

SPX-RED025 Sleeve adapter for 25mm² set-screw contact
SPX-RED035 Sleeve adapter for 35mm² set-screw contact
SPX-RED050 Sleeve adapter for 50mm² set-screw contact
SPX-RED070 Sleeve adapter for 70mm² set-screw contact
SPX-RED095 Sleeve adapter for 95mm² set-screw contact

PART NUMBER EXPLANATION

Chain Pilot Box



Patented **Chain Pilot** connectors with microswitches are employed in our Chain Pilot Box

Example Part Number

SPB **4** **D** **04** **EU** **D** **H** **S**



Series

SPB Chain Pilot box version

Maximum Current Rating

4 480amp

7 750amp

Inside Connectors Style

D Drain

S Source

Poles compositions

04 L1 - L2 - L3 - PE

05 L1 - L2 - L3 - N - PE

22 Pos - Neg / Pos - Neg

Insulator Colors

EU Europe

AU Australia

UK United Kingdom

US United States

DC Two Batteries unit (Red - Black / Red - Black)

Included accessories

D IP67 Protection caps

Contact Versions

H Threaded M12 hole

P Threaded M12 post

Box Height

S 2 units

F 2,5 units

Compatible accessories to be ordered separately

SPX-SYLOCK SyntaxLock quick secondary lock release system

Spare parts

SPXDSCS-SC-IP67 IP67 protection cap for source connectors

SPXDSCD-SC-IP67 IP67 protection cap for drain connectors


SPXTKEY Secondary lock release key

PART NUMBER EXPLANATION

PowerSyntax 45 Panel connectors



Patented Chain Pilot connectors with microswitches can be employed in our PowerSyntax 45 series



Connector Series

SCP Chain Pilot version
SPX Basic version

Maximum Current Rating

4 Up to 480amp
7 Up to 750amp

Connector Style

PD Panel Drain
PS Panel Source

Key Composition

E Earth
N Neutral
1 Phase 1
2 Phase 2
3 Phase 3

Insulator Color

GN Green
BL Blue
BR Brown
BK Black
GY Gray
RD Red
YE Yellow
WH White

Contact Version

M02 Threaded M12 hole

Connector Version

4500 PowerSyntax 45

Compatible accessories to be ordered separately

SPX-SYLOCK SyntaxLock quick secondary lock release system
SPXTKEY Secondary lock release key

SPXDCS-SC IP53 Protective plastic cap kit for source connectors
SPXD-SC IP53 Protective plastic cap kit for drain connectors
SPXDCS-SC-IP67 IP67 protection cap for source connectors
SPXD-SC-IP67 IP67 protection cap for drain connectors

PART NUMBER EXPLANATION

PowerSyntax 90 Panel connectors



Patented **Chain Pilot** connectors with microswitches can be employed in our PowerSyntax 90 series

Example Part Number

SCP 4 PD E GN M12 9000

CONNECTOR SERIES	SCP
MAXIMUM CURRENT RATING	4
CONNECTOR STYLE	PD
KEY COMPOSITION	E
INSULATOR COLOR	GN
CONTACT VERSION	M12
CONNECTOR VERSION	9000

Connector Series

SCP Chain Pilot version
SPX Basic version

Maximum Current Rating

4 Up to 480amp
7 Up to 750amp

Connector Style

PD Panel Drain
PS Panel Source

Key Composition

E Earth
N Neutral
1 Phase 1
2 Phase 2
3 Phase 3

Insulator Color

GN Green
BL Blue
BR Brown
BK Black
GY Gray
RD Red
YE Yellow
WH White

Contact Version

M12 Threaded M12 post

Connector Version

9000 PowerSyntax 90

Compatible accessories to be ordered separately

SPX-SYLOCK SyntaxLock quick secondary lock release system
SPXTKEY Secondary lock release key

SPXDCS-SC IP53 Protective plastic cap kit for source connectors

SPXDCE-SC IP53 Protective plastic cap kit for drain connectors

SPXDCS-SC-IP67 IP67 protection cap for source connectors


SPXDCE-SC-IP67 IP67 protection cap for drain connectors

PART NUMBER EXPLANATION

Lug Converters with SPY ComLug and EasiLug contacts - Line version

Example Part Number

SPY 4 LD E GN 1L 120 MQ



Connector Series

SPY for Lug Series

Maximum Current Rating

4 Up to 480amp (25 to 150mm²)

7 Up to 750amp (185 to 300mm²)

Connector Style

LD Line Drain

LS Line Source

Key Composition

E Earth

N Neutral

1 Phase 1

2 Phase 2

3 Phase 3

Insulator Color

GN Green 

BL Blue 

BR Brown 

BK Black 

GY Gray 

RD Red 

YE Yellow 

WH White 

Lug contact type and body

0L EasiLug without lug terminal (standard body)

1L EasiLug with lug terminal (standard body)

8L ComLug L Threaded M12 (standard body)

9H ComLug L2 Threaded M12 (oversized body)

9L ComLug XL Threaded M12 (oversized body)

Cable Conductor size for EasiLug terminal

000 Without EasiLug terminal / For ComLug L or XL

120 120 mm² aluminum cable

150 150 mm² aluminum cable

185 185 mm² aluminum cable

240 240 mm² aluminum cable

300 300 mm² aluminium cable

Cable Gland

M0 NO cable gland

MP Reduced M40 gland Ø 15-23 mm

MQ Normal M40 gland Ø 19-28 mm

MR Oversized M40 gland Ø 22-32 mm

MU M50 gland Ø 30-38 mm

Special versions

00 No special version

Compatible accessories, to be ordered separately

SPX-SYLOCK SyntaxLock quick secondary lock release system

SPXTKEY Secondary lock release key

SPXDCS-SC IP53 Protective plastic cap kit for source connectors

SPXD-SC IP53 Protective plastic cap kit for drain connectors

SPXDCS-SC-IP67 IP67 protection cap for source connectors


SPXD-SC-IP67 IP67 protection cap for drain connectors

PART NUMBER EXPLANATION

Lug Converters with SPY ComLug and EasiLug contacts - Panel version

Example Part Number

SPY 4 PD E GN 1L 120 MQ



Connector Series

SPY for Lug Series

Maximum Current Rating

4 Up to 480amp (25 to 150mm²)

7 Up to 750amp (185 to 300mm²)

Connector Style

PD Panel Drain

PS Panel Source

Key Composition

E Earth

N Neutral

1 Phase 1

2 Phase 2

3 Phase 3

Insulator Color

GN Green

BL Blue

BR Brown

BK Black

GY Gray

RD Red

YE Yellow

WH White

Lug contact type

0L EasiLug without lug terminal

1L EasiLug with lug terminal

8L ComLug L Threaded M12 480amp

9H ComLug L2 Threaded M12

9L ComLug XL Threaded M12

Cable Conductor size for EasiLug terminal

000 Without EasiLug terminal / For ComLug L or XL

120 120 mm² aluminum cable

150 150 mm² aluminum cable

185 185 mm² aluminum cable

240 240 mm² aluminum cable

300 300 mm² aluminium cable

SHELTER Special Versions with backshell

00 Connector body without backshell thread

M0 Backshell without cable gland (EasiLug only)

MQ Threaded body with backshell and reduced M40 gland Ø 15-23 mm (EasiLug only)

MP Threaded body with backshell and normal M40 gland Ø 19-28 mm (EasiLug only)

MR Threaded body with backshell and oversized M40 gland Ø 22-32 mm (EasiLug only)

MU Threaded body with backshell, M40-M50 adaptor M50 gland Ø 30-38 mm (EasiLug only)

(please contact us for more information about the sizes)

Special versions

00 No special version

Compatible accessories, to be ordered separately

SPX-SYLOCK SyntaxLock quick secondary lock release system

SPXTKEY Secondary lock release key

SPXDCS-SC IP53 Protective plastic cap kit for source connectors

SPXDCCD-SC IP53 Protective plastic cap kit for drain connectors

SPXDCS-SC-IP67 IP67 protection cap for source connectors

SPXDCCD-SC-IP67 IP67 protection cap for drain connectors



Tell us what you need and we'll build it for you

In our mechanical workshop we are free to innovate and independently create and test new solutions, thanks to highly skilled designers and state-of-the-art machines.
An ability of ours and a great advantage for our clients.

From basic customizations to whole new connector designs,
we are ready to give shape to your needs.


Let's discuss your new idea together.



www.valentininet.com



**Genuine
Italian
Products**



VALENTINI

Via Asti 84/A
10098 Rivoli (TO) Italy
Tel: +39 0119594160

info@syntaxnet.it
www.valentininet.com
www.powersyntaxconnectors.com
[linkedin.com/company/valentinigroup](https://www.linkedin.com/company/valentinigroup)

SYNTAX®



PowerSyntax website